








24V LED Drivers

Constant Voltage Drivers









LEDs using these drivers require a 24V DC constant voltage input with a parallel wiring method. Max 10m.

Example fittings that use these drivers include: LD Picture Light, LD Flexi, LD11, LD Line 15, LD22

24V Constant Voltage Drivers						
	TXDA24008	TXDL24020DIM	TXDO24020	TXDO24075	TXDL24150	TXDL24200
Output Power (W)	8W	20W	20W	75W	150W	200W
Dimmable	use with Dimming Contoller	use with Dimming Contoller	use with Dimming Contoller	use with Dimming Contoller	use with Dimming Contoller	use with Dimming Contoller
Output Voltage (V)	24V DC	24V DC	24V DC	24V DC	24V DC	24V DC
Dimensions L x W x H (mm)	69 x 35 x 21	110 x 52 x 24	109 x 50 x 35	220 x 46.2 x 43.6	300 x 65 x 42	300 x 65 x 42
IP Rating	Drivers can be supplied in an IP rated box for use in wet environments.					

24V Constant Voltage Mains Dimmable Drivers	
	TXDEC24050PHD
Output Power (W)	50W
Dimmable	240V leading edge dimmable
Output Voltage (V)	24V DC
Dimensions L x W x H (mm)	174 X 61 X 24
IP Rating	Drivers can be supplied in an IP rated box for use in wet environments.

Please Note: Dimming controllers must be tested with the mains dimmable driver to assess for suitability and for smooth dimming.

24V Dimming Controllers								
	TXDO-DIM	TXDO-DIM DALI	TXDO-DIM RGB	TXDO-DIM RGB DMX	TXDEL-DIM	TXDEL-DIM DALI	TXDEL-DIM DMX	TXDEL-DIM DMX 2CH
Output Power (W)	0 - 120W	0 - 120W	3 x 48W	3 x 48W	192W	192W	192W	192W
Number of Channels	1	1	3	3	1	1	1	2
Dimmable	1 - 10V (0 - 100%)	DALI (0 - 100%)	1 - 10V (0 - 100%)	DMX (0 - 100%)	0-10V (0 - 100%)	DALI (0 - 100%)	DMX (0 - 100%)	DMX (0 - 100%)
Output Voltage (V)	24V DC	24V DC	24V DC	24V DC	24V DC	24V DC	24V DC	24V DC
Dimensions L x W x H (mm)	172 x 42 x 20	172 x 42 x 20	172 x 42 x 20	172 x 42 x 20	153 x 50 x 23	153 x 50 x 23	153 x 50 x 23	153 x 50 x 23
IP Rating	Dimming controllers can be supplied in an IP rated box for use in wet environments.							