

LD40



Miniature Shallow LED Wall and Down Light

Data sheet


LD40 is an incredibly shallow downlight for applications where a very small recess depth is required. Originally designed as a special for under cabinet lighting, it has now been added to our standard range as it has proved so popular.

Key Features

- Very shallow, only 22mm recess depth required including cable
- Ideal for shelf lighting or under cabinets
- 93 CRI LED in warm white
- Range of beam angles
- Maximum output is 500mA 1.7W due to its small size
- Minimal bezel thickness
- Available with Switch, 0-10V, DMX, Dali or Mains dimmable drivers

Specification

Applications



Beam Angles 12°, 31°, 48°, 36° x 12°

LED type 1 x Cree XPG2

Colour temperature 2700K** / 3000K | 5000K

Drive Current (mA)	350	500	350	500
--------------------	-----	-----	-----	-----

LED power* (W)	1.2W	1.7W	1.2W	1.7W
----------------	------	------	------	------

CRI (typical)	93	93	75	75
---------------	----	----	----	----

Forward voltage (V) ₁₀₀	3.0V	3.2V	3.0V	3.2V
------------------------------------	------	------	------	------

Delivered lumens** (L ₁₀₀)	88	120	107	146
--	----	-----	-----	-----

Lumens per circuit watt	73	71	89	86
-------------------------	----	----	----	----

LED lifetime (to 70% lumen maintenance) 50,000hrs at a max ambient temperature of 35°C

Materials Machine finish 316 stainless steel bezel

Glass 5mm thick borosilicate




Wiring Comes pre-wired with 2 single 100mm leads, can be specified with up to 10m at extra cost

IP rating IP67


*LED wattage includes losses associated with using an 85% efficient driver

**2700K lumen output is 12% lower than the 3000K figure listed
4000K lumen output is 14% higher than the 3000K figure listed (80CRI)

Dimensions and Fixing Options



(Dimensions in mm)



Order Codes and Options

Product code	LED colour	Lens angle	Finish	Fixing
LD40 - 350 - 500				

Example: LD40-350/ LW30 / MB / White / SC

Product codes with output options

1.2W LED at 350mA	LD40-350
1.7W LED at 500mA	LD40-500

LED colour options

LED colour options	Suffix
Super Warm White (2200K)	/LW22
Extra warm white (2700K)	/LW27
Warm white (3000K)	/LW30
White (4000K) - on request	/LW40
Cool white (5000K)	/LW50
Blue	/LB
Green	/LG
Red	/LR
Amber	/LA

*Other LED colour temperatures are available. Please speak to a member of our sales team.

Beam / lens angle options

12° narrow spot	/NB
31° medium	/MB
48° wide	/WB
36° x 12° oval	/OB

Bezel finish options

Stainless steel 316
Polished and passivated stainless steel (for marine environments)
Paint finish silver / black / white (RAL 9016) / antique bronze / satin antique brass / satin brass / RAL finish

Fixing options

Spring clips	/SC
--------------	-----

Use with 350mA constant current LED drivers

We have a wide range of dimmable LED drivers, 0-10V, DMX, DALI and Mains dimmable. Please see the downloads section on our website:

To run 1-14 LD40-350 in series use a TXDEL350D (0-10V dimmable)

To run 1-14 LD40-500 in series use a TXDEL500D (0-10V dimmable)